

130CLL.1-R1186



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or general lighting.

Circular design in diameter 200mm.

High-purity sandblasted anodised aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.

Die-cast aluminium trim accessory with flush glass and silicone rubber gasket to increase the protection rating to IP65 | IK07 from underneath [reference M2.E0200]. Polycarbonate diffuser as accessory to achieve IK10 protection.

Glass ring accessory available in assorted colours [reference F1.A0200].

Drop glass disk accessory available in assorted colours [reference M1.A0200].

Drop metal disk accessory available in assorted colours [reference M1.B0200].

Decorative LED ring accessory available in assorted colours [reference F1.B0200].

LED module Tunable White: 2700K-6500K.

Remote driver supplied.

Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: $PstLM \leq 1$ and $SVM \leq 0.4$.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 30mm.

Luminaire luminous flux: 1445lm

Luminaire connected power: 19,8 W

Light source luminous flux: 1980lm

Light source power: 16 W

Constant Current: 500 mA

CRI: >90

Colour Temperature: 2700K-6500K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 37°

LOR: 73%

LED reliability at nominal Ta = 25°C: 60.000h L90B10

UGR: $C0^\circ = 13,8$ | $C90^\circ = 13,4$ under the below indicated parameters


Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.25m

Photobiological safety group: 1

This product contains a light source of energy efficiency class E

**Electronic Equipment**

T: Tunable White DALI-2/switchDIM/ColourSwitch

*Add the suffix **-T** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.10.2025]

5 years guarantee

BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com