# KAUTTA 100

IP40 Recessed linear downlights

ROVASI
Positive Lighting

## 130KTA.1-I1123

IP40 | 650º | +RAL | +MODULAR | 292 x 47mm

Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting.
Linear fixture in 303mm length and in a width of 58mm.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
PMMA optics for controlling and directing the light.
Highly efficient linear printed circuit board.
Accessories available to create customized linear systems.
Built-in driver, included.
Electronic options for lighting control: DALI-2.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
Passive temperature management.
Ceiling-mounted using steel support with screws.
Pre-wiring of 35cm cable 3x1mm2.
Other options available:
Frameless recessed.
Surface mounted.
Pendant.
Wall-mounted.
Projector.
It is possible to combine different lengths and junction modules in different ways to create customized design.




| ▼M | ▼Ø | ▼LUX |
|---|---|---|
| 1 | 0.75 | 409 |
| 2 | 1.50 | 102 |
| 3 | 2.3 | 45 |
| 4 | 3.0 | 26 |
| 5 | 3.8 | 16.4 |

**Luminaire luminous flux:** 581lm
**Luminaire connected power:** 4.81 W
**Luminaire efficiency:** 121 lm/W
**Light source luminous flux:** 625lm
**Light source power:** 3.21 W
**Constant Current:** 150 mA
**CRI:** 80
**Colour Temperature:** 3000K
**Chromaticity Tolerance:** MacAdam 3
**Beam Angle:** 43º
**LOR:** 93%
**LED reliability at nominal Ta = 25ºC:** >60000h L80B10
**Photobiological safety group:** 1
**Cd/Klm:** 704
**This product contains a light source of energy efficiency class** C

**Electronic Equipment**
**S:** On/Off
**D:** DALI-2/switchDIM/corridorFUNCTION

*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

**Finishes**
**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

**Upgradeable, Replaceable, Repairable**






Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 06.06.2025]

**5 years guarantee**

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

**ROVASI S.L.**
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

**Contact**
T. +34 93 881 35 12
T. +34 93 881 37 13
info@rovasi.com
**www.rovasi.com**