ALNAIR OUTDOOR 600

IP65 Wall-mounted fixtures

ROVASI
Positive Lighting



611ALO.04.00-I2129

IP65 | IK10 | 750º | +RAL

Wall-mounted downlights with symmetrical light distribution.
Protection rating against dust and moisture: complete IP65.
COB protected against harmful mechanical impacts: IK10.
Lampshade in diameter 400mm.
Silicone optic to control and direct the light.
Lampshade and aluminium body coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
Removable lampshade that can be easily replaced with another design or finish.
Built-in driver, included.
Electronic options for lighting control: DALI-2.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
Temperature resistant silicone rubber gaskets.
IP67 venting valve to reduce condensation.
A4 stainless steel locking screw.
Passive temperature management: heat dissipation flows through aluminium heat sink.
Mounting to the wall through mounting plate with three fixing holes.
Cable entry from the mounting plate.
Pre-wiring of 10cm 3x1mm2.
IP68 connector to be ordered separately [reference F3.A3 (On/Off) / F3.A5 (DALI-2)].

Luminaire luminous flux: 475lm
Luminaire connected power: 11,9 W
Luminaire efficiency: 40 lm/W
Light source luminous flux: 1980lm
Light source power: 10,66 W
Constant Current: 350 mA
CRI: >80
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 61º
LOR: 24%
LED reliability at nominal Ta = 25ºC: 60.000h L90B10
Photobiological safety group: 1
This product contains a light source of energy efficiency class D



▼M	▼Ø	▼LUX	61°
1	1.19	659	
2	2.4	165	
3	3.6	73	
4	4.8	41	
5	5.9	26	

Electronic Equipment
S: On/Off (AC/DC, NOT looping through capable)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi [15m]

*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

Finishes
04: RAL7016: Anthracite Grey textured, **01:** RAL9010: Pure White textured, **02:** RAL9005: Jet Black textured, **07:** RAL9006: White Aluminium textured, **80:** Corten

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.10.2025]

5 years guarantee

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12
T. +34 93 881 37 13
info@rovasi.com
www.rovasi.com