




## 102JET.1.01-I2096



Projectors with symmetrical light distribution.

Cylindrical design in diameter 235mm.

Protection rating against dust and moisture: entire IP65.

Protection rating of resistance to harmful mechanical impacts: IK07.

Robust body and trim made of die-cast aluminium coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.

Double Aluminium reflectors. Bottom reflector: sandblasted metalized. Top reflector: faceted metalized or sandblasted metalized depending on the beam angle output.

5 mm tempered protection glass clear as standard, other finishes under request.

Polycarbonate diffuser as option to achieve IK10 protection degree.

Temperature resistant silicone rubber gasket.

IP67 venting valve to reduce condensation.

A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0235+F2.A1].

Built-in driver, included. Ambient temperature: up to 50°C.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0,4.

Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through the fixture body itself or through interior aluminium heat sink.

Mounting to the ceiling or to the wall by support with two securing holes that enables the device to be swivelled and adjusted to achieve specific lighting effects.

Cable entry from the top of the fixture.

**Luminaire luminous flux:** 2200lm

**Luminaire connected power:** 17,1 W

**Luminaire efficiency:** 129 lm/W

**Light source luminous flux:** 2785lm

**Light source power:** 15,43 W

**Constant Current:** 500 mA

**CRI:** >80

**Colour Temperature:** 2700K

**Chromaticity Tolerance:** MacAdam 3

**Beam Angle:** 13°


**LOR:** 79%

**LED reliability at nominal Ta = 25°C:** 100.000h L90B10

**Photobiological safety group:** 1

**Cd/Klm:** 8898

**This product contains a light source of energy efficiency class D**



### Electronic Equipment

**S:** On/Off (AC/DC, NOT looping through capable)

**SE:** On/Off (AC/DC) + Battery 3h

**D:** DALI-2/switchDIM/corridorFUNCTION


**DE:** DALI-2/switchDIM/corridorFUNCTION + 3 hours battery

**B:** Bluetooth-Casambi [ 10m ]

\*Add the suffix **-S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

### Finishes

**Upgradeable, Replaceable, Repairable**  
1: RAL9005 Pure White textured, 2: RAL9005 Jet Black textured, 3: RAL9005 Jet Black textured, 4: RAL7016 Anthracite Grey textured, 5: RAL9006 White Aluminium textured, 6: RAL9006 White Aluminium textured, 7: RAL9006 White Aluminium textured, 8: RAL9006 White Aluminium textured, 9: RAL6005 Moss Green textured



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 12.12.2025]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

### Contact

T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 **www.rovasi.com**