



101STR.1.02-R2004



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Circular design in diameter 150mm.

Protection rating against dust and moisture: IP54 from underneath.

White painted aluminium reflector. Sandblasted metalized aluminium reflector available as option.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.

Intermediate tempered frosted glass .

Remote driver supplied.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0,4.

Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle.

3 hours battery available as option (class I).

Passive temperature management: heat dissipation flows through aluminium heat sink.

Ceiling-mounted by spring clamps for easy installation.

Luminaire luminous flux: 974lm

Luminaire connected power: 11,9 W

Luminaire efficiency: 82 lm/W

Light source luminous flux: 1650lm

Light source power: 10,66 W

Constant Current: 350 mA

CRI: >90 R9 64

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 65°

LOR: 59%

LED reliability at nominal Ta = 25°C: 60.000h L90B10

UGR: C0° = 23,5 | C90° = 23,5 under the below indicated parameters

Room dimensions X=4H/8H


Reflectance 20% | 50% | 70%

Luminaire spacing = 0.25m

Photobiological safety group: 1

Cd/Klm: 819

This product contains a light source of energy efficiency class D



Electronic Equipment

K: On/Off (basic)

S: On/Off (AC/DC + looping through)

SE: On/Off (AC/DC+looping) + 3h battery

D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h

B: Bluetooth-Casambi

*Add the suffix **-K**, **-S**, **-SE**, **-D**, **-DE**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 16.01.2026]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com