



101TRG.1-R2009



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or general lighting.
Triangular design in 216mm side.
Protection rating against dust and moisture: IP54 from underneath.
High-purity matt anodised aluminium reflector.
Powder painted aluminium frame available in assorted finishes, customized RAL under request.
Frosted protection glass.
Remote driver included.
Electronic options for lighting control: DALI-2 or Bluetooth.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.
3 hours battery available as option (class I).
Passive temperature management: heat dissipation flows through an aluminium heat sink.
Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.

Luminaire luminous flux: 1280lm
Luminaire connected power: 17,1 W
Luminaire efficiency: 75 lm/W
Light source luminous flux: 2285lm
Light source power: 15,43 W
Constant Current: 500 mA
CRI: >90 R9 62
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 82°
LOR: 56%
LED reliability at nominal Ta = 25°C: 100.000h L90B10
Photobiological safety group: 1
This product contains a light source of energy efficiency class E

Electronic Equipment
K: On/Off (basic)
S: On/Off (AC/DC + looping through)
SE: On/Off (AC/DC+looping) + 3h battery
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h
B: Bluetooth-Casambi



*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 09.09.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com