

## 101TSQ.8.01-I2109



Recessed buried uplight with symmetrical light distribution.  
 Square design with dimensions 340mm x 340 mm.  
 IP68 protection rating that enables it to resist immersion to a depth of 1m.  
 Protection rating for resistance to harmful mechanical impacts: IK10.  
 Load supported: 4200Kg. It can be driven over by vehicles with pneumatic tyres.  
 Robust and corrosion-resistant black painted aluminium housing with C5-M special coating for environments with very high corrosivity. Frame made of 316L stainless steel marine grade.  
 High-purity matt anodised aluminium reflector.  
 15 mm tempered protection glass clear as standard, other finishes under request.  
 Skid-blocking safety glass finishing for public areas walked by pedestrians can be supplied under request [reference F2.C0340].  
 Temperature resistant silicone rubber gasket.  
 A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0340+F2.A1].  
 Built-in driver, included.  
 Electronic options for lighting control: DALI-2.  
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.  
 Passive temperature management: heat dissipation flows through the fixture body itself.  
 Supplied with aluminium insertion tube as standard. Insertion tube for flush installation as accessory [reference M3.D0340].  
 Ground mounted with two fixing holes.  
 Double cable gland entry for installation in series.  
 Pre-wiring of 0.5 metres cable 3x1mm<sup>2</sup>.  
 IP68 connector to be ordered separately [reference F3.A3 (On/Off) / F3.A5 (DALI) ].

**Luminaire luminous flux:** 3729lm  
**Luminaire connected power:** 37,1 W  
**Luminaire efficiency:** 101 lm/W  
**Light source luminous flux:** 6015lm  
**Light source power:** 33,4 W  
**Constant Current:** 1050 mA  
**CRI:** >80  
**Colour Temperature:** 3000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 58°  
**LOR:** 62%  
**LED reliability at nominal Ta = 25°C:** 60.000h L90B10  
**Photobiological safety group:** 1  
**Cd/Klm:** 710

**This product contains a light source of energy efficiency class C**

### Electronic Equipment


**S:** On/Off (AC/DC)  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**B:** Bluetooth-Casambi [ 15m ]

\*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

### Finishes

**8:** Stainless Steel 316L: Marine grade, **1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

### Upgradeable, Replaceable, Repairable



### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 13.06.2025]

### 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
 BSI Cert ISO 14001:2015 - n°EMS 554685

### ROVASI S.L.

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

### Contact

T. +34 93 881 35 12 info@rovasi.com  
 T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)