



350TRT.1-I1439



Surface mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.
 Linear fixture in 287mm length and in a width of 40mm.
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
 Opal extruded polycarbonate diffuser.
 Highly efficient linear printed circuit board.
 Accessories available to create customized linear systems.
 Built-in driver, included.
 Electronic options for lighting control: DALI-2 or Bluetooth.
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.
 Passive temperature management.
 Ceiling-mounted using cleats.
 It is possible to combine different lengths and junction modules in different ways to create customized systems.

Luminaire luminous flux: 536lm
Luminaire connected power: 7,9 W
Luminaire efficiency: 68 lm/W
Light source luminous flux: 850lm
Light source power: 5,41 W
Constant Current: 250 mA
CRI: >90 R9 57
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 91°
LOR: 63%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

UGR: C0° = 24,9 | C90° = 24,9 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.25m

Photobiological safety group: 0

This product contains a light source of energy efficiency class D

Electronic Equipment


S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

**Upgradeable, Replaceable, Repairable****Note**

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 08.10.2025]

5 years guarantee

BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12
 T. +34 93 881 37 13

info@rovasi.com

www.rovasi.com