



250BRS.1-I1428



Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.
 Frameless linear fixture in 287mm length and in a width of 44mm.
 Protection rating against dust and moisture: complete IP54.
 Protection rating of resistance to harmful mechanical impacts: IK08.
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
 Opal polycarbonate diffuser.
 Highly efficient linear printed circuit board.
 Built-in driver, included.
 Electronic options for lighting control: DALI-2 or Bluetooth.
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: $PstLM \leq 1$ and $SVM \leq 0.4$.
 Passive temperature management.
 Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm².
 Accessory for serial installation, reference F3.L2.BRS.

Luminaire luminous flux: 323lm
Luminaire connected power: 5,7 W
Luminaire efficiency: 57 lm/W
Light source luminous flux: 610lm
Light source power: 3,2 W
Constant Current: 150 mA
CRI: >80
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 100°
LOR: 53%
LED reliability at nominal Ta = 25°C: 100.000h L80B10
UGR: $C0^\circ = 24,9$ | $C90^\circ = 24,2$ under the below indicated parameters
 Room dimensions $X=4H/8H$
 Reflectance 20% | 50% | 70%
 Luminaire spacing = 0.25m
Photobiological safety group: 0
This product contains a light source of energy efficiency class C



Electronic Equipment

S: On/Off
D: DALI-2/switchDIM
B: Bluetooth-Casambi

*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 09.10.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
 T. +34 93 881 37 13 www.rovasi.com