# GOWEL 400

IP20 Pendant linear downlights

ROVASI
Positive Lighting




## 401GWL.1-I1717

IP20 | IK06 | 650º | +RAL | 3.78Kg

Pendant linear downlights with symmetrical light distribution to achieve an effective task or general lighting.
Linear fixture in 581mm length and in a width of 70mm.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
Range of PMMA optics to achieve specific photometric results.
Highly efficient linear printed circuit board.
Accessories available to create customized linear systems.
Built-in driver, included.
Electronic options for lighting control: DALI-2.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
Passive temperature management.
Ceiling-mounted with adjustable steel wire suspension ( 1m ) and transparent electrical wire. Different suspension length on request.
It is possible to combine different lengths and junction modules in different ways to create customized systems.

**Luminaire luminous flux:** 5187lm
**Luminaire connected power:** 35,5 W
**Luminaire efficiency:** 146 lm/W
**Light source luminous flux:** 5700lm
**Light source power:** 32 W
**Constant Current:** 500 mA
**CRI:** 80
**Colour Temperature:** 5000K
**Chromaticity Tolerance:** MacAdam 3
**Beam Angle:** 17º
**LOR:** 91%
**LED reliability at nominal Ta = 25ºC:** 72.000h L80B10
**Photobiological safety group:** 1
**Cd/Klm:** 6350
**This product contains a light source of energy efficiency class** C




| ▼M | ▼Ø | ▼LUX | 17º |
|---|---|---|---|
| 1 | 0.30 | 32940 | |
| 2 | 0.60 | 8235 | |
| 3 | 0.91 | 3660 | |
| 4 | 1.21 | 2059 | |
| 5 | 1.51 | 1318 | |

**Electronic Equipment**
**S:** On/Off (AC/DC)
**D:** DALI-2/switchDIM/corridorFUNCTION
**B:** Bluetooth-Casambi

*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

**Finishes**
**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

**Upgradeable, Replaceable, Repairable**






Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.07.2025]

**5 years guarantee**

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

**ROVASI S.L.**
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

**Contact**
T. +34 93 881 35 12
T. +34 93 881 37 13
info@rovasi.com
**www.rovasi.com**