




851HRN.1-I1612



Linear projectors with symmetrical light distribution to achieve an effective task or general lighting.
 Frameless linear fixture in 576mm length and in a width of 50mm.
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
 Range of PMMA optics to achieve specific photometric results.
 Highly efficient linear printed circuit board.
 Built-in driver, included.
 Electronic options for lighting control: DALI-2.
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.
 Passive temperature management.
 Ceiling-mounted using adjustable supports.
 Matching products:
 HORIZON 100 recessed.
 HORIZON 300 surface mounted.
 HORIZON 400 and HORIZON 500 pendant.
 HORIZON 600 and HORIZON 700 wall-mounted.

Luminaire luminous flux: 2305lm
Luminaire connected power: 17 W
Luminaire efficiency: 136 lm/W
Light source luminous flux: 2505lm
Light source power: 13,8 W
Constant Current: 500 mA
CRI: 80
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 78°
LOR: 92%

LED reliability at nominal Ta = 25°C: 54.000h L80B10
Photobiological safety group: 1
Cd/Klm: 698

This product contains a light source of energy efficiency class C


Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi

*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 14.06.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
 T. +34 93 881 37 13 www.rovasi.com