





330KTA.1-I1428



Surface mounted linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting.
 Linear fixture in 287mm length and in a width of 44mm.
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
 PMMA optics for controlling and directing the light.
 Highly efficient linear printed circuit board.
 Accessories available to create customized linear systems.
 Built-in driver, included.
 Electronic options for lighting control: DALI-2 or Bluetooth.
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.
 Passive temperature management.
 Ceiling-mounted using cleats.
 Other options available:
 Recessed.
 Frameless recessed.
 Pendant.
 Wall-mounted.
 Projectors.
 It is possible to combine different lengths and junction modules in different ways to create customized design.

Luminaire luminous flux: 567lm
Luminaire connected power: 5,7 W
Luminaire efficiency: 99 lm/W
Light source luminous flux: 610lm
Light source power: 3,2 W
Constant Current: 150 mA
CRI: >80
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 43°
LOR: 93%
LED reliability at nominal Ta = 25°C: 100.000h L80B10
UGR: C0° = 19,3 | C90° = 24,8 under the below indicated parameters
 Room dimensions X=4H/8H
 Reflectance 20% | 50% | 70%
 Luminaire spacing = 0.25m
Photobiological safety group: 0
Cd/Klm: 704
This product contains a light source of energy efficiency class C

**Electronic Equipment****S:** On/Off**D:** DALI-2/switchDIM/corridorFUNCTION*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.**Finishes****1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium**Upgradeable, Replaceable, Repairable****Note**

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 31.10.2025]

5 years guarantee

BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12
 T. +34 93 881 37 13

info@rovasi.com
 www.rovasi.com