# KAUTTA 800

IP40 Projectors

ROVASI
Positive Lighting




## 836KTA.1-I1540

IP40 | 650º | +RAL

Linear projectors with symmetrical light distribution to achieve an effective accent, task or general lighting.
Linear fixture in 1408mm length and in a width of 44mm.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
PMMA optics for controlling and directing the light.
Highly efficient linear printed circuit board.
Built-in driver, included.
Electronic options for lighting control: DALI-2.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
3 hours battery available as option.
Passive temperature management.
Ceiling or wall installation with adjustable fixing brackets.
Other options available:
Recessed.
Frameless recessed.
Surface-mounted.
Pendant.
Wall-mounted.




| ▼M | ▼Ø | ▼LUX | 43° |
|---|---|---|---|
| 1 | 0.79 | 2053 | |
| 2 | 1.58 | 513 | |
| 3 | 2.4 | 228 | |
| 4 | 3.2 | 128 | |
| 5 | 3.9 | 82 | |

**Luminaire luminous flux:** 2846lm
**Luminaire connected power:** 17,71 W
**Luminaire efficiency:** 161 lm/W
**Light source luminous flux:** 3060lm
**Light source power:** 16 W
**Constant Current:** 150 mA
**CRI:** >80
**Colour Temperature:** 2700K
**Chromaticity Tolerance:** MacAdam 3
**Beam Angle:** 43º
**LOR:** 93%
**LED reliability at nominal Ta = 25ºC:** 100.000h L80B10
**Photobiological safety group:** 0
**Cd/Klm:** 704
**This product contains a light source of energy efficiency class** C

**Electronic Equipment**
**S:** On/Off (AC/DC)
**SE:** On/Off (AC/DC) + Battery 3h
**D:** DALI-2/switchDIM/corridorFUNCTION
**DE:** DALI-2/switchDIM+ 3 hours battery
**DDE:** DALI-2/switchDIM+ 3 hours battery (DALI)
**B:** Bluetooth-Casambi

*Add the suffix **-S, -SE, -D, -DE, -DDE, -B** after the reference to indicate your electronic equipment choice.

**Finishes**
**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

**Upgradeable, Replaceable, Repairable**






Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.07.2025]

**5 years guarantee**

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

**ROVASI S.L.**
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

**Contact**
T. +34 93 881 35 12
T. +34 93 881 37 13
info@rovasi.com
**www.rovasi.com**