



539KTA.1-I1570



Pendant linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting. Double light emission: up and down.
 Linear fixture in 2808mm length and in a width of 44mm.
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
 PMMA optics for controlling and directing the light.
 Highly efficient linear printed circuit board.
 Accessories available to create customized linear systems.
 Built-in driver included
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4 .
 Electronic options for lighting control: DALI-2 (two DALI addresses) .
 3 hours battery available as option.
 Passive temperature management.
 Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request.
 Other options available:
 Frameless.
 Frameless recessed.
 Surface-mounted
 Wall-mounted.
 It is possible to combine different lengths and junction modules in different ways to create customized design.

Luminaire luminous flux: 8447lm

Luminaire connected power: 35,42+27 W

Light source luminous flux: 6470lm+3000lm

Light source power: 32+24 W

Constant Current: 150 mA

CRI: >80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 43°


LOR: 93%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 0

Cd/Klm: 704

This product contains a light source of energy efficiency class B



Electronic Equipment

S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h

D: DALI-2/switchDIM/corridorFUNCTION

D: DALI-2/switchDIM(two DALI-2 addresses)

DE: DALI-2/switchDIM+ 3 hours battery


B: Bluetooth-Casambi

*Add the suffix **-S**, **-SE**, **-D**, **-D**, **-DE**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 08.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
 T. +34 93 881 37 13 www.rovasi.com