KAUTTA 700

Two-sided emission IP20 Wall-mounted linear fixtures

ROVASI
Positive Lighting



733KTA.1-I1497

IP20 | 650º | +RAL

Wall mounted linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting. Double light emission: up and down.
Linear fixture in 848mm length and in a width of 44mm.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
PMMA optics for controlling and directing the light.
Highly efficient linear printed circuit board.
Accessories available to create customized linear systems.
Built-in driver included
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
Electronic options for lighting control: DALI-2 .
Passive temperature management.
Wall mounted by mounting brackets.
Other options available:
Recessed.
Frameless recessed.
Pendant.
Surface mounted.
Projectors.
>It is possible to combine different lengths and junction modules in different ways to create customized design.



▼M	▼Ø	▼LUX	41°
1	0.76	1850	
2	1.52	463	
3	2.3	206	
4	3.0	116	
5	3.8	74	

Luminaire luminous flux: 3158lm
Luminaire connected power: 18,04+10 W
Light source luminous flux: 2665lm+840lm
Light source power: 16,23+6,65 W
Constant Current: 250 mA
CRI: >90 R9 54
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 43º
LOR: 93%
LED reliability at nominal Ta = 25ºC: 100.000h L80B10
UGR: C0º = 20,6 | C90º = 26,3 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.25m
Photobiological safety group: 0
Cd/Klm: 704
This product contains a light source of energy efficiency class D

Electronic Equipment
S: On/Off (AC/DC, NOT looping through capable)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi

*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.10.2025]

5 years guarantee

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12
T. +34 93 881 37 13
info@rovasi.com
www.rovasi.com