



121GOR.1-I1610



Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Specially developed to solve the installation difficulties in the process of replacing linear luminaires using old fluorescent lamps in metal ceiling systems.

Customized exterior dimensions depending on the installation needs.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

The adaptation sheet is fixed to the light fixture to create a single body for easier installation.

Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic standard options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0,4.

Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle.

Passive temperature management.

Ceiling-mounted using galvanised steel brackets.

Pre-wiring of 35cm cable 3x1mm².

Luminaire luminous flux: 1843lm

Luminaire connected power: 12,4 W

Luminaire efficiency: 149 lm/W

Light source luminous flux: 1900lm

Light source power: 9,4 W

Constant Current: 350 mA

CRI: 80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 31°

LOR: 97%

LED reliability at nominal Ta = 25°C: 54.000h L80B10

UGR: C0° = 17,1 | C90° = 17,1 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.25m

Photobiological safety group: 1

Cd/Klm: 2060

This product contains a light source of energy efficiency class B

Electronic Equipment

S: On/Off (AC/DC, NOT looping through capable)


D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 11.01.2026]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com