


123DRK.1-I1626




Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.  
Specially developed to solve the installation difficulties in the process of replacing linear luminaires using old fluorescent lamps.  
Customized exterior dimensions depending on the installation needs.  
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.  
The adaptation sheet is fixed to the light fixture to create a single body for easier installation.  
Range of PMMA optics to achieve specific photometric results.  
Highly efficient linear printed circuit board.  
Built-in driver, included.  
Electronic standard options for lighting control: DALI-2 or Bluetooth.  
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.  
Passive temperature management.  
Ceiling-mounted using galvanized steel support with screws.  
Pre-wiring of 35cm cable 3x1mm<sup>2</sup>.

**Luminaire luminous flux:** 5340lm  
**Luminaire connected power:** 33 W  
**Luminaire efficiency:** 162 lm/W  
**Light source luminous flux:** 5505lm  
**Light source power:** 30 W  
**Constant Current:** 700 mA  
**CRI:** 80  
**Colour Temperature:** 5000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 31°  
**LOR:** 97%  
**LED reliability at nominal Ta = 25°C:** 54.000h L80B10  
**Photobiological safety group:** 1  
**Cd/Klm:** 2060  
**This product contains a light source of energy efficiency class B**


**Electronic Equipment**  
**S:** On/Off (AC/DC, NOT looping through capable)  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**B:** Bluetooth-Casambi

\*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

**Finishes**  
**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.09.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12    info@rovasi.com  
T. +34 93 881 37 13    www.rovasi.com