

# BAFFLE EVOLUTION

Small recessed downlights

**ROVASI**  
Positive Lighting



## 101BFV.1-R2310



Recessed ceiling-mounted small downlight with symmetrical light distribution to achieve an effective accent lighting.

Circular design in diameter 66mm, interior aperture in diameter 45mm.

Internal cylindrical aluminium black baffle for minimal glare.

Deep regressed light source to ensure visual comfort.

Powder painted trim available in assorted finishes, customized RAL under request.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0066].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Remote driver included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits:  $PstLM \leq 1$  and  $SVM \leq 0.4$ .

Passive temperature management: heat dissipation flows through an aluminium heat sink diffuser.

Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm.

**Luminaire connected power:** 7,25 W

**Light source luminous flux:** 725lm

**Light source power:** 6,68 W

**Constant Current:** 200 mA

**CRI:** >90 R9 69

**Colour Temperature:** 3000K

**Chromaticity Tolerance:** MacAdam 3

**Beam Angle:** 12°

**LED reliability at nominal Ta = 25°C:** >54000h L90B50

**Photobiological safety group:** 1

**This product contains a light source of energy efficiency class F**

### Electronic Equipment

**K:** On/Off (basic)

**S:** On/Off (AC/DC)

**SE:** On/Off (AC/DC) + Battery 3h

**D:** DALI-2/switchDIM/corridorFUNCTION

**DE:** DALI-2/switchDIM + 3h battery

**B:** Bluetooth-Casambi

\*Add the suffix **-K**, **-S**, **-SE**, **-D**, **-DE**, **-B** after the reference to indicate your electronic equipment choice.

### Finishes

**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

### Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 14.06.2025]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

### Contact

T. +34 93 881 35 12    info@rovasi.com  
T. +34 93 881 37 13    **www.rovasi.com**