



## 101HDN.1-R2309



Recessed ceiling-mounted multiDirectional downlights with symmetrical light distribution to achieve an effective task, accent or general lighting.

Square design in 110mm x 110mm.

Swivel mounted downlights, adjustable up to 25° and with 180° rotation.

Die-cast aluminium trim and recessing surface powder painted in assorted finishes, customized RAL under request.

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted with spring clamps for easy installation.

**Luminaire connected power:** 7,25 W

**Light source luminous flux:** 685lm

**Light source power:** 6,68 W

**Constant Current:** 200 mA

**CRI:** >90 R9 54

**Colour Temperature:** 2700K

**Chromaticity Tolerance:** MacAdam 3

**Beam Angle:** 12°

**LED reliability at nominal Ta = 25°C:** >54000h L90B50

**Photobiological safety group:** 1

**This product contains a light source of energy efficiency class F**

#### Electronic Equipment

**K:** On/Off (basic)

**S:** On/Off (AC/DC, NOT looping through capable)

**SE:** On/Off (AC/DC) + Battery 3h

**D:** DALI-2/switchDIM/corridorFUNCTION

**DE:** DALI-2/switchDIM + 3h battery

**B:** Bluetooth-Casambi

\*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

#### Finishes

**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.08.2025]

#### 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

#### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

#### Contact

T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)