



101CHS.1-R2319



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or general lighting.

Square frameless design for plasterboard ceilings available in 80mm.

Powder painted body available in assorted finishes, customized RAL under request.

To complete the effect of this luminaire, it is suggested that the interior be painted the same RAL colour as the ceiling.

Honeycomb louver accessory to improve visual comfort [reference M6.A0050].

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0070].

Remote driver included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4 .

3 hours battery available as option.

Passive temperature management: heat dissipation flows through aluminium heat sink diffuser.

Mounted to the ceiling by two fixing points with screws.

Luminaire connected power: 9,14 W

Light source luminous flux: 880lm

Light source power: 8,52 W

Constant Current: 250 mA

CRI: >90 R9 69

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 12°

LED reliability at nominal Ta = 25°C: >54000h L90B50

Photobiological safety group: 1

This product contains a light source of energy efficiency class F

Electronic Equipment

K: On/Off (basic)

S: On/Off (AC/DC, NOT looping through capable)

SE: On/Off (AC/DC) + Battery 3h

D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.09.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com