DISTRICT 600

IP66 Wall mounted linear downlights

ROVASI
Positive Lighting



654DSX.4.01-I1401

IP66 | IK10 | 650º | 50º | +RAL

Wall mounted linear fixtures with symmetrical light distribution.
Linear fixture in 155mm length, width of 62mm and height of 85mm.
Protection rating against dust and moisture: complete IP66.
Protection rating for resistance to harmful mechanical impacts: IK10.
Extruded aluminium profile coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
Highly efficient linear printed circuit board.
Protection polycarbonate diffuser in 4mm.
Interior frosted polycarbonate diffuser.
Built-in driver, included. Ambient temperature: up to 50ºC.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
IP67 venting valve to reduce condensation.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw.
Wall-mounted by 316L stainless steel mounting brackets.
The electric cable inlet is on one end of the fixture.
Passive temperature management.

Luminaire luminous flux: 146lm
Luminaire connected power: 4,1 W
Luminaire efficiency: 36 lm/W
Light source luminous flux: 305lm
Light source power: 1,6 W
Constant Current: 150 mA
CRI: >80
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 100º
LOR: 48%
LED reliability at nominal Ta = 25ºC: 100.000h L80B10
Photobiological safety group: 0
This product contains a light source of energy efficiency class C



▼M	▼Ø	▼LUX
1	2.4	63
2	4.7	15.7
3	7.1	7.0
4	9.5	3.9
5	11.8	2.5

100°

Electronic Equipment
S: On/Off
D: DALI-2/switchDIM

*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes
4: RAL7016: Anthracite Grey textured, **1:** RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **7:** RAL9006: White Aluminium textured, **80 Corten:**, **90:** RAL6005 Moss Green textured

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.07.2025]

5 years guarantee

CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12
T. +34 93 881 37 13
info@rovasi.com
www.rovasi.com