




250KBR.11-I2902



IP20

650°






Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.
 Frameless linear fixture in 284mm length and in a width of 50mm.
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
 White finish darklight reflector in 7 cells designed to ensure visual comfort.
 Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.
 Highly efficient linear printed circuit board.
 Built-in driver, included.
 Electronic options for lighting control: DALI-2 or Bluetooth.
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: $PstLM \leq 1$ and $SVM \leq 0.4$.
 Passive temperature management.
 Ceiling-mounted using steel support with screws. It is possible to combine different lengths and junction modules in different ways to create customized design.

Luminaire luminous flux: 706lm**Luminaire connected power:** 6,7 W**Luminaire efficiency:** 105 lm/W**Light source luminous flux:** 720lm**Light source power:** 4,7 W**Constant Current:** 250 mA**CRI:** 90**Colour Temperature:** 2700K**Chromaticity Tolerance:** MacAdam3**Beam Angle:** 78°**LOR:** 98%**LED reliability at nominal Ta = 25°C:** 90.000h L80B10**UGR:** $C0^\circ = 17,6$ | $C90^\circ = 17,5$ under the below indicated parametersRoom dimensions $X=4H/8H$

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.25m

Photobiological safety group: 1**This product contains a light source of energy efficiency class D****Electronic Equipment****S:** On/Off**D:** DALI-2/switchDIM**B:** Bluetooth-Casambi*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.**Finishes****11:** White frame - white reflector**Upgradeable, Replaceable, Repairable****Note**

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.10.2025]

5 years guarantee

BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12
 T. +34 93 881 37 13

info@rovasi.com
www.rovasi.com