


150LMA.42-I1206



Recessed linear downlights with symmetrical light distribution.
 Linear fixture in 309mm length, width of 75mm and height of 85mm.
 Protection rating against dust and moisture: complete IP66.
 Protection rating for resistance to harmful mechanical impacts: IK10.
 Extruded aluminium profile coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
 Highly efficient linear printed circuit board.
 Protection polycarbonate diffuser in 4mm.
 Black finish modular optics in 7 cells designed to ensure visual comfort.
 Built-in driver included.
 Electronic options for lighting control: DALI-2.
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: $PstLM \leq 1$ and $SVM \leq 0.4$.
 IP67 venting valve to reduce condensation.
 A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw.
 Ceiling-mounted using steel support with screws.
 The electric cable inlet is on one end of the fixture.
 Pre-wiring of 35cm cable 3x1mm².
 Concrete housing in galvanised metal accessory reference F3.F0309DSX.
 Passive temperature management.

Luminaire luminous flux: 348lm
Luminaire connected power: 3,97 W
Luminaire efficiency: 88 lm/W
Light source luminous flux: 570lm
Light source power: 2,8 W
Constant Current: 150 mA
CRI: 80
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam3
Beam Angle: 67°
LOR: 61%
LED reliability at nominal Ta = 25°C: 90.000h L80B10
Photobiological safety group: 1
This product contains a light source of energy efficiency class B

**Electronic Equipment**

S: On/Off
D: DALI-2/switchDIM
B: Bluetooth-Casambi

*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

+ **C5-M:** special coating for very high corrosivity environments, **42:** RAL7016 Anthracite Grey - black reflector

Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.09.2025]

5 years guarantee

BSI Cert ISO 9001:2015 - n°FM 39346
 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
 T. +34 93 881 37 13 **www.rovasi.com**