


101TER.8.02-E231



Recessed buried uplight with symmetrical light distribution.  
 Circular design in diameter: 120mm.  
 IP67 protection rating that enables it to resist immersion to a depth of 1m.  
 Protection rating of resistance to harmful mechanical impacts: IK10.  
 Load supported: 6600 Kg. It can be driven over by vehicles with pneumatic tyres.  
 Robust and corrosion-resistant black painted aluminium housing with C5-M special coating for environments with very high corrosivity. 316L stainless steel marine grade trim.  
 Sandblasted metalized aluminium reflector.  
 10 mm tempered protection frosted glass.  
 Temperature resistant silicone rubber gasket.  
 A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0120 + F2.A1].  
 Remote driver supplied.  
 Passive temperature management: heat dissipation flows through the fixture body itself.  
 Ground mounted by two fixing holes.  
 Supplied with aluminium insertion tube as standard. Insertion tube for flush installation as accessory [reference M3.C0120].  
 Pre-wiring of 0.5 metres cable 2x1,5mm2.  
 IP68 connector to be ordered separately [reference F3.A3 (On/Off)].


**Luminaire luminous flux:** 281lm  
**Luminaire connected power:** 6.3 W  
**Light source luminous flux:** 783lm  
**Constant Current:** 180 mA  
**CRI:** >80  
**Colour Temperature:** 3000K  
**Beam Angle:** 76°  
**LOR:** 36%  
**Average Service Life:** 50000h  
**Photobiological safety group:** 1



Electronic Equipment

**Finishes**  
**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **8:** Stainless Steel 316L: Marine grade, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
 BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
 Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

**Contact**  
 T. +34 93 881 35 12 info@rovasi.com  
 T. +34 93 881 37 13 www.rovasi.com