

108KUU.1.02-I646



Recessed ceiling mounted downlights with symmetrical light distribution to achieve an effective ambient lighting.  
Circular design available in 395mm diameter.  
Powder painted aluminium trim available in assorted finishes, customized RAL under request.  
PMMA opal diffuser (thickness 3mm).  
Tridonic high energy efficiency printed circuit board.  
Built-in driver, included.  
Electronic options for lighting control: DALI-2.  
Passive temperature management: heat dissipation flows through the fixture body itself.  
Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.  
KUU can be combined with PLACE pendant downlights and LEDA surface-mounted downlights to get a harmonious finish.

**Luminaire luminous flux:** 3208lm  
**Luminaire connected power:** 24.56 W  
**Luminaire efficiency:** 131 lm/W  
**Light source luminous flux:** 3685lm  
**Light source power:** 23 W  
**Constant Current:** 800 mA  
**CRI:** >80  
**Colour Temperature:** 4000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 114°  
**LOR:** 87%

**Average Service Life:** 50000h  
**LED reliability:** >50000 L90B10  
**UGR:** <19 under the below indicated parameters  
Room dimensions X=4H/8H  
Reflectance 20% | 50% | 70%  
Luminaire spacing = 0.55m  
**Photobiological safety group:** 1  
**Cd/Klm:** 345  
**Imax:** 1105 Cd

**This product contains a light source of energy efficiency class C**

**Electronic Equipment**




**S:** On/Off (AC/DC)  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**B:** Bluetooth-Casambi

\*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

**Finishes**

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

**Upgradeable, Replaceable, Repairable**



**Note**

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)