




101BXS.1-R944



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.
 Round design with trimless appearance in diameter 72mm.
 Aluminium body and interior circle powder painted in various finishes, customized RAL under request.
 To complete the effect of this luminaire, it is suggested that the circle be painted the same RAL colour as the ceiling.
 Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].
 Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].
 Remote driver included.
 Electronic options for lighting control: DALI-2.
 3 hours battery available as option*.
 Passive temperature management: heat dissipation via aluminium heat sink.
 Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 656lm
Luminaire connected power: 7.4 W
Luminaire efficiency: 89 lm/W
Light source luminous flux: 965lm
Light source power: 6.7 W
Constant Current: 200 mA
CRI: >90
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 17°
LOR: 68%

Average Service Life: 50000h
LED reliability: >51000h L80B10
UGR: <19 under the below indicated parameters
 Room dimensions X=4H/8H
 Reflectance 20% | 50% | 70%
 Luminaire spacing = 0.6m
Photobiological safety group: 1
Cd/Klm: 5192

This product contains a light source of energy efficiency class E



Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery
B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

**Upgradeable, Replaceable, Repairable****Note**

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - n°FM 39346
 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
 T. +34 93 881 37 13 www.rovasi.com