

## 102PLN.1-R871



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.  
Circular design in diameter 133mm.  
Flush installation, the fixture is completely fitted in the ceiling void. Installation in plasterboard ceilings.  
Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. To complete the effect of this fixture, it is also recommended that the trim should be painted the same RAL colour as the ceiling.  
Facetted metalized aluminium reflector.  
Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.  
Glass accessory available to increase the protection rating to IP54 | IK05 from underneath [reference M2.B0133].  
Remote driver supplied.  
Electronic options for lighting control: DALI-2.  
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.  
3 hours battery available as option (class I).  
Passive temperature management: heat dissipation flows through aluminium heat sink.  
Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.

**Luminaire luminous flux:** 2721lm  
**Luminaire connected power:** 18.33 W  
**Luminaire efficiency:** 148 lm/W  
**Light source luminous flux:** 2990lm  
**Light source power:** 17 W  
**Constant Current:** 500 mA  
**CRI:** >80  
**Colour Temperature:** 4000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 24°  
**LOR:** 91%  
**Average Service Life:** 50000h  
**LED reliability:** 50000h L90B10  
**UGR:** <16  
**Photobiological safety group:** 1  
**Cd/Klm:** 3580  
**Imax:** 10704 Cd

**This product contains a light source of energy efficiency class D**

### Electronic Equipment


**K:** On/Off (basic)  
**S:** On/Off (AC/DC + looping through)  
**SE:** On/Off (AC/DC+looping) + 3h battery  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**DE:** DALI-2/switchDIM/corridorFUNCTION + Battery 3h  
**B:** Bluetooth-Casambi

\*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

### Finishes

**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

### Upgradeable, Replaceable, Repairable



### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 09.05.2025]

### 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

### Contact

T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)