


137RCK.1-I907



Wall mounted luminaires with symmetrical light distribution to achieve an effective task or general lighting. Neutral cylindrical body in diameter 60mm. Sandblasted metalized aluminium reflector silver finished. Powder painted aluminium profile available in assorted finishes, customized RAL under request. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4. Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself. Wall mounted by aluminium mounting plate with two fixing points. Cable entry through the aluminium wall mounting plate. ROCKET can be combined with the KERI pendant line and the GOTA surface mounted fixtures to get a harmonious finish.

Luminaire luminous flux: 534lm
Luminaire connected power: 4.8 W
Luminaire efficiency: 111 lm/W
Light source luminous flux: 905lm
Light source power: 137RCK.1-I907_137RCK.1-I907V
Constant Current: 150 mA
CRI: >80
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 22°
LOR: 59%
Average Service Life: 50000h
LED reliability: 50000h L90B10
Photobiological safety group: 1
This product contains a light source of energy efficiency class A++



Electronic Equipment
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -D after the reference to indicate your electronic equipment choice.

Finishes
2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.05.2024]