

## 336KTA.1-I807



Surface mounted linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting.

Linear fixture in 1408mm length and in a width of 44mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optics for controlling and directing the light.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq 1$  and SVM  $\leq 0.4$ .

3 hours battery available as option.

Passive temperature management.

Ceiling-mounted using cleats.

Other options available:

Recessed.

Frameless recessed.

Pendant.

Wall-mounted.

Projectors.

It is possible to combine different lengths and junction modules in different ways to create customized design.

**Luminaire luminous flux:** 2711lm

**Luminaire connected power:** 17.76 W

**Luminaire efficiency:** 153 lm/W

**Light source luminous flux:** 2915lm

**Light source power:** 16 W

**Constant Current:** 150 mA

**CRI:** 80

**Colour Temperature:** 2700K

**Chromaticity Tolerance:** MacAdam 3

**Beam Angle:** 43°

**LOR:** 93%

**Average Service Life:** 50000h

**LED reliability:** >60000h L80B10

**UGR:** <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%


Luminaire spacing = 0.3m

**Photobiological safety group:** 1

**Cd/Klm:** 704

**Imax:** 2052 Cd

**This product contains a light source of energy efficiency class D + C**



## Electronic Equipment

**S:** On/Off (AC/DC)

**SE:** On/Off (AC/DC) + Battery 3h

**D:** DALI-2/switchDIM/corridorFUNCTION

**DE:** DALI-2/switchDIM+ 3 hours battery

**DDE:** DALI-2/switchDIM+ 3 hours battery (DALI)



**B:** Bluetooth-Casambi

\*Add the suffix **-S**, **-SE**, **-D**, **-DE**, **-DDE**, **-B** after the reference to indicate your electronic equipment choice.

## Finishes

**Upgradeable, Replaceable, Repairable**

**1:** RAL9006: White Aluminium, **2:** RAL9005: Black, **3:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium



## Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 30.04.2025]

## 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

## ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

## Contact

T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 www.rovasi.com