

101KPL.1-R524



Small recessed ceiling-mounted downlights with asymmetrical light distribution to achieve an effective accent lighting.

Circular design in diameter 85mm, slot interior aperture with 17mm radius.

Internal cylindrical aluminium black baffle for minimal glare.

Deep regressed module to ensure visual comfort.

Tilt version, adjustable to 30°.

Powder painted trim available in assorted finishes, customized RAL under request.

This fixture is available in IP65 | IK07 protection from underneath, KEPLER SEAL.

Accessory available to increase the IP protection to IP54 | IK05 from underneath [reference M2.G0085].

Remote driver included.

Electronic options for lighting control: DALI-2.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm.

Luminaire luminous flux: 358lm

Luminaire connected power: 5.66 W

Luminaire efficiency: 63 lm/W

Light source luminous flux: 560lm

Light source power: 5 W

Constant Current: 150 mA

CRI: >90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 21°

LOR: 64%


Average Service Life: 50000h

LED reliability: >50000h L70B50

UGR: <16

Photobiological safety group: 1

This product contains a light source of energy efficiency class F



Electronic Equipment

K: On/Off (basic)

S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h

D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

*Add the suffix **-K**, **-S**, **-SE**, **-D**, **-DE**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com