


101KPS.1.01-R641



Small recessed ceiling-mounted downlight with asymmetrical light distribution to achieve an effective accent lighting.  
Protection rating against dust and moisture: IP65 from underneath.  
Circular design in diameter 85mm, slot interior aperture with 17mm radius.  
Internal cylindrical aluminium black baffle for minimal glare.  
Deep regressed module to ensure visual comfort.  
Adjustable baffle, tilt up to 30°.  
Powder painted trim available in assorted finishes, customized RAL under request.  
Glass and silicone rubber gasket to ensure IP65 protection from underneath.  
Remote driver included.  
Electronic options for lighting control: DALI-2.  
3 hours battery available as option.  
Passive temperature management: heat dissipation flows through an aluminium heat sink.  
Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm.

**Luminaire luminous flux:** 570lm  
**Luminaire connected power:** 9.77 W  
**Luminaire efficiency:** 58 lm/W  
**Light source luminous flux:** 890lm  
**Light source power:** 8.8 W  
**Constant Current:** 250 mA  
**CRI:** >90  
**Colour Temperature:** 4000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 21°  
**LOR:** 64%  
**Average Service Life:** 50000h  
**LED reliability:** >50000h L70B50  
**UGR:** <19  
**Photobiological safety group:** 1  
**This product contains a light source of energy efficiency class F**



Electronic Equipment


**K:** On/Off (basic)  
**S:** On/Off (AC/DC)  
**SE:** On/Off (AC/DC) + Battery 3h  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**DE:** DALI-2/switchDIM + 3h battery  
**B:** Bluetooth-Casambi

\*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 www.rovasi.com