



110PLC.1.02-I721



Pendant downlights with symmetrical light distribution to achieve an effective ambient lighting.
Circular design available in 835mm diameter.
Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.

PMMA opal diffuser (thickness 3mm.).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 2700K - 6500K

Built-in driver, included.

Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0,4.

Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle.

Passive temperature management: heat dissipation flows through the fixture body itself.

Ceiling-mounted using ceiling rose. Suspended 1 meter by four steel cords. Transparent electronic wire.

PLACE can be combined with KUU and CANDRA recessed downlights and LEDA surface-mounted downlights to get a harmonious finish.

Luminaire luminous flux: 6605lm

Luminaire connected power: 59,9 W

Luminaire efficiency: 110 lm/W

Light source luminous flux: 9610lm

Light source power: 58 W

Constant Current: 250 mA

CRI: >90

Colour Temperature: 2700K-6500K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 102°

LED reliability at nominal Ta = 25°C: 50.000h L90B50

Photobiological safety group: 1

This product contains a light source of energy efficiency class D


Electronic Equipment

T: Tunable White DALI-2/switchDIM/ColourSwitch

*Add the suffix **-T** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.01.2026]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com