

304MOV.1-I869



Surface-mounted spots with symmetrical light distribution to achieve an effective task, accent or general lighting.

Cylindrical design in diameter 90 mm.

Articulated arm adjustable 0°, 15°, 30°, 45°, 60°, 75° and 90° and with 355° rotation around the vertical axis.

Facetted metalized or sandblasted metalized aluminium reflector.

Powder painted aluminium body and arm available in assorted finishes, customized RAL under request.

Aluminium base for attachment to the ceiling supplied with the same finish as the light fixture.

Optional anti-glare accessories for more visual comfort.

Integral driver included.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounted to the ceiling by two fixing points.

**Luminaire luminous flux:** 2066lm

**Luminaire connected power:** 18.33 W

**Luminaire efficiency:** 113 lm/W

**Light source luminous flux:** 2755lm

**Light source power:** 17 W

**Constant Current:** 500 mA

**CRI:** >80

**Colour Temperature:** 2700K

**Chromaticity Tolerance:** MacAdam 3

**Beam Angle:** 19°

**LOR:** 75%


**Average Service Life:** 50000h

**LED reliability:** 50000h L90B10

**UGR:** <19

**Photobiological safety group:** 1

**This product contains a light source of energy efficiency class D**



**Electronic Equipment**

**K:** On/Off (basic)

**S:** On/Off (AC/DC)


**D:** DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix **-K**, **-S**, **-D** after the reference to indicate your electronic equipment choice.

**Finishes**

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

**Upgradeable, Replaceable, Repairable**



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 12.05.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**

T. +34 93 881 35 12    info@rovasi.com  
T. +34 93 881 37 13    **www.rovasi.com**