



## 101QTC.1-R1152



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.  
 Square design available in 225mm x 225mm.  
 High-purity matt anodised aluminium reflector.  
 Powder painted die-cast aluminium frame available in assorted finishes, customized RAL under request.  
 Glass accessory available to increase the protection rating to IP54 | IK05 from underneath [reference M2.D0225].  
 Drop square glass accessory available in assorted colours [reference M1.C0225].  
 Drop square metal accessory available in assorted colours [reference M1.E0225].  
 LED frame accessory available in assorted colours [reference M1.D0225].  
 Remote driver supplied. LED module for special applications.  
 Electronic options for lighting control: DALI-2 or Bluetooth.  
 The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits:  $PstLM \leq 1$  and  $SVM \leq 0.4$ .  
 Passive temperature management: heat dissipation flows through aluminium heat sink.  
 Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.

**Luminaire luminous flux:** 1336lm  
**Luminaire connected power:** 12.61 W  
**Light source luminous flux:** 1610lm  
**Light source power:** 11 W  
**Constant Current:** 350 mA  
**CRI:** 97  
**Colour Temperature:** ART 3000K  
**Chromaticity Tolerance:** MacAdam 2  
**Beam Angle:** 72°  
**LOR:** 83%  
**LED reliability at nominal Ta = 25°C:** 100.000h L90B10  
**Photobiological safety group:** 1  
**Cd/Klm:** 684  
**This product contains a light source of energy efficiency class F**



### Electronic Equipment


**K:** On/Off (basic)  
**S:** On/Off (AC/DC + looping through)  
**SE:** On/Off (AC/DC+looping) + 3h battery  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**DE:** DALI-2/switchDIM/corridorFUNCTION + Battery 3h  
**B:** Bluetooth-Casambi

\*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

### Finishes

**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

### Upgradeable, Replaceable, Repairable



### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 08.09.2025]

### 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346  
 BSI Cert ISO 14001:2015 - n°EMS 554685

### ROVASI S.L.

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

### Contact

T. +34 93 881 35 12 info@rovasi.com  
 T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)