


101KSS.1-I874



Surface-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.  
Facetted metallized aluminium reflector to control and direct the light.  
Powder painted aluminium body available in assorted finishes, customized RAL under request.  
Built-in driver, included.  
Electronic options for lighting control: DALI-2.  
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.  
Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.  
Mounting to the ceiling plate with three securing holes. Cable entry from the top of the luminaire.

**Luminaire luminous flux:** 2321lm  
**Luminaire connected power:** 18.33 W  
**Luminaire efficiency:** 127 lm/W  
**Light source luminous flux:** 2550lm  
**Light source power:** 17 W  
**Constant Current:** 500 mA  
**CRI:** >90  
**Colour Temperature:** 4000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 12°  
**LOR:** 91%  
**Average Service Life:** 50000h  
**LED reliability:** 50000h L90B10  
**UGR:** <16  
**Photobiological safety group:** 1  
**Cd/Klm:** 9093  
**Imax:** 23187 Cd  
**This product contains a light source of energy efficiency class E**



**Electronic Equipment**


**S:** On/Off  
**D:** DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

**Finishes**

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

**Upgradeable, Replaceable, Repairable**



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.05.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)