


105LDA.1.02-I659



Surface-mounted downlights with symmetrical light distribution to achieve an effective ambient lighting.
Circular design available in 835mm diameter.
Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.
Polycarbonate opal diffuser (thickness 3mm.).
Tridonic high energy efficiency printed circuit board.
Tridonic built-in driver, included.
Electronic standard options for lighting control: DALI/ DSI.
Emergency kit as option (change of size required).
Passive temperature management: heat dissipation flows through the fixture body itself.
Mounting to the ceiling plate with four securing points. Cable entry from the top of the fixture.
LEDA can be combined with PLACE pendant downlights and KUU and CANDRA recessed downlights to get a harmonious finish.

Magnitude data

Power: 60 W
Constant Current: 500 mA
Luminous flux: 10725lm
CRI: >80
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Average Service Life: 50000h
LED reliability: L90B10 >50000h
UGR: 22
Energy efficiency class: A++

Electronic equipment

S: On/Off
D: DALI/DSI/switchDIM/corridorFUNCTION
SE: On/Off +E-Kit
DE: DALI/DSI/SwitchDIM/corridorFUNCTION+E-Kit
DDE: DALI/DSI/switchDIM/corridorFUNCTION+E-Kit (DALI)

There are accessories available for dimming devices.

*Add the suffix **-S, -D, -SE, -DE, -DDE** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **3:** Satin Bronze, **4:** RAL7016: Anthracite Grey, **5:** RAL1036: Pearl Gold Bright, **6:** Metallic Lacquer RAL9022: Chrome, **7:** RAL9006: White Aluminium

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.10.2017]

