



101ADP.1-R871/_/_/_



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or general lighting.

Specially developed to solve the installation difficulties in the process of replacing light fixtures.

Customized exterior trim diameter from 140 mm up to 170 mm, depending on the installation needs.

This luminaire is suitable for recessed diameters ranging from 130mm to 159mm.

High-purity aluminium reflector sandblasted metalized.

Powder painted aluminium trim available in assorted finishes, customized RAL under request.

Remote driver supplied.

Electronic standard options for lighting control: DALI-2 or Bluetooth.

Passive temperature management: heat dissipation via aluminium heatsink.

Ceiling-mounted using galvanised steel support with spring clamps for an easy installation.

Luminaire luminous flux: 2512lm
Luminaire connected power: 18.33 W
Luminaire efficiency: 137 lm/W
Light source luminous flux: 2990lm
Light source power: 17 W
Constant Current: 500 mA
CRI: >80
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 105°
LOR: 84%

Average Service Life: 50000h

LED reliability: 50000h L90B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.85m

Photobiological safety group: 1

Cd/Klm: 387

Imax: 1157 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic)

S: On/Off (AC/DC + looping through)

SE: On/Off (AC/DC+looping) + 3h battery

D: DALI-2/switchDIM/corridorFUNCTION


DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h

B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
 T. +34 93 881 37 13 www.rovasi.com