
# KIBRI 400

# IP20 Pendant linear downlights







## 455KBR.22-I1235



Pendant linear downlights with symmetrical light distribution to achieve an effective task or general

Linear fixture in 1124mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. darklight reflector in 28 cells in black finish designed to ensure visual comfort.

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request. It is possible to combine different lengths and junction modules in different ways to create customized design.

Imax=1346 Cd

750

η=100.0% ▼ M ▼ Ø ▼ LUX

1.61 1340

1

2 3.2 335

3 4.8 149

4 6.4 84

5 8.0 54 78°

Luminaire luminous flux: 1947lm Luminaire connected power: 14,54 W Luminaire efficiency: 134 lm/W Light source luminous flux: 2140lm Light source power: 11,2 W Constant Current: 150 mA

**CRI:** 80

Colour Temperature: 3000K Chromaticity Tolerance: MacAdam3

Beam Angle: 78° **LOR:** 91%

LED reliability at nominal Ta = 25°C: 90.000h L80B10 **UGR:**  $C0^\circ = 15,9 \mid C90^\circ = 15,8$  under the below indicated parameters Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

#### **Electronic Equipment**

S: On/Off (AC/DC, NOT looping through capable) SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM+ 3 hours battery
DDE: DALI-2/switchDIM+ 3 hours battery (DALI)

B: Bluetooth-Casambi

\*Add the suffix -S, -SE, -D, -DE, -DDE, -B after the reference to indicate your electronic equipment choice.

## **Finishes**

22: Black frame - Black reflector

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.11.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASIS.L.**

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13