
# KIBRI 500

# Two-sided emission IP20 pendant linear fixtures







# 561KBR.14-I1215



Pendant linear downlights with symmetrical light distribution to achieve an effective task or general

Two sides light emission: downlight and uplight.Linear fixture in 284mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Metallised darklight reflector in 14 cells in silvered finish in silvered finish designed to ensure visual

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, separate switching up and down.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request. It is possible to combine different lengths and junction modules in different ways to create customized design.

Imax=453 Cd

η=100.0% ▼ M ▼ Ø ▼LUX

2 4.1 109

3 6.2 48

4 8.3 27

2.1 434

10.4 17.4 92°

Luminaire luminous flux: 974lm Luminaire connected power: 8,35 W Luminaire efficiency: 117 lm/W Light source luminous flux: 1070lm

Light source power: 5,6 W Constant Current: 150 mA

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam3

Beam Angle: 92° **LOR:** 91%

**LED** reliability at nominal Ta = 25°C: 90.000h L80B10 **UGR:**  $C0^{\circ} = 16,4 \mid C90^{\circ} = 17,2$  under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

## **Electronic Equipment**

**S:** On/Off (AC/DC, NOT looping through capable) **D:** DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

#### **Finishes**

14: White frame - Silver reflector

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.10.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASIS.L.**

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13