
# KIBRI 500

# Two-sided emission IP20 pendant linear fixtures







# 565KBR.11-I1235



Pendant linear downlights with symmetrical light distribution to achieve an effective task or general

Two sides light emission: downlight and uplight.Linear fixture in 844mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. White finish darklight reflector in 28 cells designed to ensure visual comfort.

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, separate switching up and down.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request. It is possible to combine different lengths and junction modules in different ways to create customized design.

lmax=850 Cd

450

η=100.0% ▼ M ▼ Ø ▼LUX

1 2.2

2 4.4 194

3 6.7

4

11.1 31 96°

777

49 8.9

Luminaire luminous flux: 1969lm Luminaire connected power: 14,54 W Luminaire efficiency: 135 lm/W Light source luminous flux: 2140lm Light source power: 11,2 W Constant Current: 150 mA

**CRI:** 80

Colour Temperature: 3000K Chromaticity Tolerance: MacAdam3

Beam Angle: 96° LOR: 92%

LED reliability at nominal Ta = 25°C: 90.000h L80B10 **UGR:**  $C0^{\circ} = 17,1 \mid C90^{\circ} = 17,8$  under the below indicated parameters Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

#### **Electronic Equipment**

S: On/Off (AC/DC, NOT looping through capable) SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM+ 3 hours battery
DDE: DALI-2/switchDIM+ 3 hours battery (DALI)

B: Bluetooth-Casambi

\*Add the suffix -S, -SE, -D, -DE, -DDE, -B after the reference to indicate your electronic equipment choice.

## **Finishes**

11: White frame - white reflector

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.11.2025]

5 years guarantee



Spain

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13