
# KIBRI 900







## 950KBR.11-I1210



Linear downlights with 3-phase track adapter with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 284mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

White finish modular optics in 7 cells designed to ensure visual comfort.

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits:  $PstLM \le 1$  and  $SVM \le 0.4$ .

lmax=606 Cd

200

η=100.0% ▼ M ▼ Ø ▼ LUX

1

4 6.5 38

1.63 604

3.3 151

8.1 24

78°

Passive temperature management.

Three-phase tracks are available as well as accessories to create a custom system.

Luminaire luminous flux: 916lm Luminaire connected power: 6,7 W Luminaire efficiency: 137 lm/W Light source luminous flux: 935lm Light source power: 4,7 W Constant Current: 250 mA

**CRI:** 80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam3

Beam Angle: 78° LOR: 98%

LED reliability at nominal Ta = 25°C: 90.000h L80B10

Photobiological safety group: 1

This product contains a light source of energy efficiency class B

### **Electronic Equipment**

S: On/Off

D: DALI-2/switchDIM

B: Bluetooth-Casambi

\*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

#### **Finishes**

11: White frame - white reflector

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 31.08.2025]

5 years guarantee



Spain

T. +34 93 881 35 12 T. +34 93 881 37 13

Contact