
# KIBRI 900







## 950KBR.11-I1212



Linear downlights with 3-phase track adapter with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 284mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

White finish modular optics in 7 cells designed to ensure visual comfort.

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

lmax=843 Cd

150

300

600

750

η=100.0% ▼ M ▼ Ø ▼ LUX

1

4 6.5 52

1.63 839

3.3 210

8.1 34 78°

limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4. Passive temperature management.

Three-phase tracks are available as well as accessories to create a custom system.

Luminaire luminous flux: 1274lm Luminaire connected power: 9,54 W Luminaire efficiency: 134 lm/W Light source luminous flux: 1300lm Light source power: 6,7 W

Constant Current: 350 mA

**CRI:** 80

Colour Temperature: 4000K Chromaticity Tolerance: MacAdam3

Beam Angle: 78° **LOR:** 98%

LED reliability at nominal Ta = 25°C: 72.000h L80B10

Photobiological safety group: 1

This product contains a light source of energy efficiency class B

### **Electronic Equipment**

S: On/Off

D: DALI-2/switchDIM

B: Bluetooth-Casambi

\*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

#### **Finishes**

11: White frame - white reflector

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 31.08.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

Spain

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13