KIBRI 900

Linear downlights with track adapter







961KBR.22-I1215



Linear downlights with 3-phase track adapter with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 564mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Modular optics in 14 cells in black finish designed to ensure visual comfort.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

lmax=383 Cd

150

η=100.0% ▼ M ▼ Ø ▼ LUX

1 2.2 355

3

4

5 10.9 14.2

4.4 89

22 8.7

95°

Passive temperature management.

Three-phase tracks are available as well as accessories to create a custom system.

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Luminaire luminous flux: 867lm Luminaire connected power: 8,35 W Luminaire efficiency: 104 lm/W Light source luminous flux: 1070lm

Light source power: 5,6 W Constant Current: 150 mA

CRI: 80

Colour Temperature: 3000K Chromaticity Tolerance: MacAdam3

Beam Angle: 96° **LOR:** 81%

LED reliability at nominal Ta = 25°C: 90.000h L80B10

UGR: <19

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

22: Black frame - Black reflector

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13