KIBRI 200

IP20 Frameless recessed linear downlights









250KBR.14-I1207











Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 284mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Metallised modular optics in 7 cells in silvered finish in silvered finish designed to ensure visual comfort. Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

Passive temperature management.

Ceiling-mounted using steel support with screws.It is possible to combine different lengths and junction modules in different ways to create customized design.

lmax=478 Cd

η=100.0% ▼M ▼Ø ▼LUX

2 3.1 119

3

4 6.3 30

1.57 476

4.7 53

7.9

Luminaire luminous flux: 682lm Luminaire connected power: 5.34 W Luminaire efficiency: 128 lm/W Light source luminous flux: 710lm Light source power: 3.7 W Constant Current: 200 mA

CRI: 80

Colour Temperature: 3000K Chromaticity Tolerance: MacAdam3

Beam Angle: 76° **LOR:** 96%

Average Service Life: 50000h LED reliability: >90.000h L80B10

UGR: 17

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off
D: DALI-2/switchDIM B: Bluetooth-Casambi

 * Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

14: White frame - Silver reflector

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13