
# KIBRI 200

## IP20 Frameless recessed linear downlights







### 251KBR.22-I1215



IP20 650°







Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 564mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. darklight reflector in 14 cells in black finish designed to ensure visual comfort.

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.

Ceiling-mounted using steel support with screws.It is possible to combine different lengths and junction modules in different ways to create customized design.

max=673 Cd

200

300

400

500

η=100.0% ▼M ▼Ø ▼LUX

2 3.2 168

3 4.8

4 6.4 42

1.61 671

8.0

75

Luminaire luminous flux: 974lm Luminaire connected power: 8,35 W Luminaire efficiency: 117 lm/W Light source luminous flux: 1070lm

Light source power: 5,6 W Constant Current: 150 mA

**CRI:** 80

Colour Temperature: 3000K Chromaticity Tolerance: MacAdam3

Beam Angle: 78° **LOR:** 91%

**LED** reliability at nominal Ta = 25°C: 90.000h L80B10 **UGR:**  $C0^{\circ} = 15.9 \mid C90^{\circ} = 15.8$  under the below indicated parameters Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

#### **Electronic Equipment**

**S:** On/Off (AC/DC, NOT looping through capable) **D:** DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

#### **Finishes**

22: Black frame - Black reflector

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 01.11.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASIS.L.**

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13