# KIBRI 200

## IP20 Frameless recessed linear downlights







### 260KBR.25-I1205









Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 284mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Metallised darklight reflector in 7 cells in golden finish designed to ensure visual comfort.

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

650°

Built-in driver, included.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.

Ceiling-mounted using steel support with screws.It is possible to combine different lengths and junction modules in different ways to create customized design.

lmax=225 Cd

120

160

η=100.0% ▼M ▼Ø ▼LUX

2

3

4 8.3 13.6

2.1 218

10.4

55 4.1

24 6.2

Luminaire luminous flux: 487lm Luminaire connected power: 3,97 W Luminaire efficiency: 123 lm/W Light source luminous flux: 535lm Light source power: 2,8 W Constant Current: 150 mA

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam3

Beam Angle: 92° **LOR:** 91%

**LED** reliability at nominal Ta = 25°C: 90.000h L80B10  $\pmb{\textbf{UGR:}}\ C0^o=18.8\ |\ C90^o=19.1\$  under the below indicated parameters Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

#### **Electronic Equipment**

S: On/Off
D: DALI-2/switchDIM

B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

#### **Finishes**

25: Black frame - golden reflector

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.11.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASIS.L.**

#### Contact

T. +34 93 881 35 12

info@rovasi.com

T. +34 93 881 37 13 www.rovasi.com