KIBRI 300



	350KBR.11-I1213
	Surface mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 284mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. White finish modular optics in 7 cells designed to ensure visual comfort.
	Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2.
	The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: $PstLM \le 1$ and $SVM \le 0.4$. Passive temperature management.
]69	Ceiling-mounted using cleats. It is possible to combine different lengths and junction modules in different ways to create customized design.
	Luminaire luminous flux: 1539lm Luminaire connected power: 12,5 W Luminaire efficiency: 123 lm/W Light source luminous flux: 1570lm Light source power: 8,8 W Constant Current: 450 mA CRI: 80 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam3
	Beam Angle: 78° LOR: 98% LED reliability at nominal Ta = 25°C: 72.000h L80B10 Photobiological safety group: 1 This product contains a light source of energy efficiency class C
	Electronic Equipment S: On/Off D: DALI-2/switchDIM B: Bluetooth-Casambi
	*Add the suffix -S , -D , -B after the reference to indicate your electronic equipment choice. Finishes
	11: White frame - white reflector
	Upgradeable, Replaceable, Repairable

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.08.2025]

СЕ BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.** Ronda de la Font Grossa, 15

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com