# KIBRI 300

## IP20 Surface mounted linear downlights



η=100.0% ▼M ▼Ø ▼LUX

2 3.1 90

3

4 6.3 22

210

1.57 358

4.7 40

7.9





### 350KBR.26-I1205



Surface mounted linear downlights with symmetrical light distribution to achieve an effective task or

Linear fixture in 284mm length and in a width of 50mm.

+RAL

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Metallised modular optics in 7 cells in Copper finish designed to ensure visual comfort.

Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.

Ceiling-mounted using cleats. It is possible to combine different lengths and junction modules in different ways to create customized design.

Luminaire luminous flux: 514lm Luminaire connected power: 3.97 W Luminaire efficiency: 129 lm/W Light source luminous flux: 535lm Light source power: 2.8 W Constant Current: 150 mA

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam3

Beam Angle: 76° **LOR:** 96%

LED reliability at nominal Ta = 25°C: 90.000h L80B10

**UGR:** 16

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

### **Electronic Equipment**

S: On/Off D: DALI-2/switchDIM B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

# **Finishes**

26: Black frame - cooper reflector

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.06.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

### **ROVASIS.L.**

#### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com