
Trimless appearance recessed downlights







190BSQ.1-R1186











Imax=2062 Cd

800

η=74.1% ▼ M ▼ Ø ▼LUX

1

2 1.87 515

3 2.8 229

4

5 4.7 82

0.93 2062

129 3.7

50°

Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Square design with trimless appearance in 177mm x 177mm.

Aluminium interior frame powder painted in assorted finishes, customized RAL under request.

To complete the effect of this fixture, it is suggested that the interior frame be painted the same RAL colour as the ceiling.

High-purity aluminium interior reflector available in assorted finishes: facetted metalized or sandblasted anodised depending on the beam angle outcome.

LED module Tunable White: 2700K to 6500K.

Remote driver supplied.

Electronic standard options for lighting control: SwitchDIM, ColourSwitch, DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM < 1 and SVM < 0.4.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Ceiling-mounted using galvanised steel support with screws.

Luminaire luminous flux: 1465lm Luminaire connected power: 19,8 W Luminaire efficiency: 74 lm/W Light source luminous flux: 1980lm

Light source power: 16 W Constant Current: 500 mA

CRI: >90

Colour Temperature: 2700K-6500K Chromaticity Tolerance: MacAdam 3

Beam Angle: 50° **LOR:** 74%

LED reliability at nominal Ta = 25°C: 60.000h L90B10 $\textbf{UGR:}\ C0^o = 17,7 \mid C90^o = 17,2 \ \ \text{under the below indicated parameters}$ Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 1

This product contains a light source of energy efficiency class F

Electronic Equipment

T: Tunable White DALI-2/switchDIM/ColourSwitch

*Add the suffix -T after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.11.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.**

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Spain

Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13