


139ADP.1-R620/_/_/_



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or general lighting.
Specially developed to solve the installation difficulties in the process of replacing light fixtures. Customized exterior trim diameter from 110 mm up to 130 mm, depending on the installation needs. This luminaire is suitable for recessed diameters ranging from 100mm to 119mm.
High-purity aluminium reflector sandbasted metalized.
Powder painted aluminium trim available in assorted finishes, customized RAL under request.
Remote driver supplied.
Electronic standard options for lighting control: DALI-2 or Bluetooth.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
Passive temperature management: heat dissipation via aluminium heatsink.
Ceiling-mounted using galvanised steel support with spring clamps for an easy installation.

Luminaire luminous flux: 622lm
Luminaire connected power: 7.69 W
Luminaire efficiency: 81 lm/W
Light source luminous flux: 720lm
Light source power: 6.6 W
Constant Current: 200 mA
CRI: >90
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 21°
LOR: 86%
Average Service Life: 50000h
LED reliability: >50000h L70B50
UGR: <16
Photobiological safety group: 1
This product contains a light source of energy efficiency class F




Electronic Equipment
K: On/Off (basic)
S: On/Off (AC/DC)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery
B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes
2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com